



## Safety Data Sheet acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

### 1 Identification

- **Product identifier**
- **Trade name:** P10 2K DTM PU PRIMER
- **Article number:** P10
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Lyquid Specialty Coatings  
176 New Highway  
N. Amityville, NY 11701
- **Information department:** Product safety department
- **Emergency telephone number:**  
24 Hrs Emergency Contact:  
INFOTRAC  
1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene  
 n-butyl acetate  
 acetone  
 titanium dioxide

- **Hazard statements**

Highly flammable liquid and vapor.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause drowsiness or dizziness.

- **Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2  
 Fire = 3  
 Reactivity = 0

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

|            |   |                |
|------------|---|----------------|
| HEALTH     | 2 | Health = 2     |
| FIRE       | 3 | Fire = 3       |
| REACTIVITY | 0 | Reactivity = 0 |

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

|            |   |         |
|------------|---|---------|
| 98-56-6    | 4-chloro-alpha,alpha,alpha-trifluorotoluene | 25-50%  |
| 123-86-4   | n-butyl acetate                             | 25-50%  |
| 67-64-1    | acetone                                     | 10-25%  |
| 110-43-0   | heptan-2-one                                | 2.5-10% |
| 1330-20-7  | xylene                                      | 2.5-10% |
| 13463-67-7 | titanium dioxide                            | 2.5-10% |
| 7727-43-7  | barium sulphate, natural                    | ≤2.5%   |

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

USA

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 3)

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

|             |  |                         |
|-------------|--|-------------------------|
| 123-86-4    | <i>n</i> -butyl acetate                | 5 ppm                   |
| 67-64-1     | acetone                                | 200 ppm                 |
| 110-43-0    | heptan-2-one                           | 150 ppm                 |
| 1330-20-7   | xylene                                 | 130 ppm                 |
| 13463-67-7  | titanium dioxide                       | 30 mg/m <sup>3</sup>    |
| 7727-43-7   | barium sulphate, natural               | 15 mg/m <sup>3</sup>    |
| 9002-88-4   | Polyethylene low density               | 16 mg/m <sup>3</sup>    |
| 112926-00-8 | Precipitated silica (Silica-Amorphous) | 18 mg/m <sup>3</sup>    |
| 1333-86-4   | Carbon black                           | 9 mg/m <sup>3</sup>     |
| 100-41-4    | ethylbenzene                           | 33 ppm                  |
| 77-58-7     | dibutyltin dilaurate                   | 1.1 mg/m <sup>3</sup>   |
| 14808-60-7  | Quartz (SiO <sub>2</sub> )             | 0.075 mg/m <sup>3</sup> |
| 57-55-6     | Propylene glycol                       | 30 mg/m <sup>3</sup>    |
| 78-83-1     | butanol                                | 150 ppm                 |
| 108-83-8    | 2,6-dimethylheptan-4-one               | 75 ppm                  |
| 108-65-6    | 2-methoxy-1-methylethyl acetate        | 50 ppm                  |
| 34590-94-8  | Dipropylene glycol monomethyl ether    | 150 ppm                 |
| 70657-70-4  | 2-methoxypropyl acetate                | 50 ppm                  |
| 67-56-1     | methanol                               | 530 ppm                 |

- **PAC-2:**

|             |  |                       |
|-------------|--|-----------------------|
| 123-86-4    | <i>n</i> -butyl acetate                | 200 ppm               |
| 67-64-1     | acetone                                | 3200* ppm             |
| 110-43-0    | heptan-2-one                           | 670 ppm               |
| 1330-20-7   | xylene                                 | 920* ppm              |
| 13463-67-7  | titanium dioxide                       | 330 mg/m <sup>3</sup> |
| 7727-43-7   | barium sulphate, natural               | 170 mg/m <sup>3</sup> |
| 9002-88-4   | Polyethylene low density               | 170 mg/m <sup>3</sup> |
| 112926-00-8 | Precipitated silica (Silica-Amorphous) | 200 mg/m <sup>3</sup> |
| 1333-86-4   | Carbon black                           | 99 mg/m <sup>3</sup>  |

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: **P10 2K DTM PU PRIMER**

(Contd. of page 4)

|            |                                     |                         |
|------------|-------------------------------------|-------------------------|
| 100-41-4   | ethylbenzene                        | 1100* ppm               |
| 77-58-7    | dibutyltin dilaurate                | 8 mg/m <sup>3</sup>     |
| 14808-60-7 | Quartz (SiO <sub>2</sub> )          | 33 mg/m <sup>3</sup>    |
| 57-55-6    | Propylene glycol                    | 1,300 mg/m <sup>3</sup> |
| 78-83-1    | butanol                             | 1,300 ppm               |
| 108-83-8   | 2,6-dimethylheptan-4-one            | 330 ppm                 |
| 108-65-6   | 2-methoxy-1-methylethyl acetate     | 1,000 ppm               |
| 34590-94-8 | Dipropylene glycol monomethyl ether | 1700* ppm               |
| 70657-70-4 | 2-methoxypropyl acetate             | 1,000 ppm               |
| 67-56-1    | methanol                            | 2,100 ppm               |

**PAC-3:**

|             |  |                         |
|-------------|--|-------------------------|
| 123-86-4    | n-butyl acetate                        | 3000* ppm               |
| 67-64-1     | acetone                                | 5700* ppm               |
| 110-43-0    | heptan-2-one                           | 4000* ppm               |
| 1330-20-7   | xylene                                 | 2500* ppm               |
| 13463-67-7  | titanium dioxide                       | 2,000 mg/m <sup>3</sup> |
| 7727-43-7   | barium sulphate, natural               | 990 mg/m <sup>3</sup>   |
| 9002-88-4   | Polyethylene low density               | 1,000 mg/m <sup>3</sup> |
| 112926-00-8 | Precipitated silica (Silica-Amorphous) | 1,200 mg/m <sup>3</sup> |
| 1333-86-4   | Carbon black                           | 590 mg/m <sup>3</sup>   |
| 100-41-4    | ethylbenzene                           | 1800* ppm               |
| 77-58-7     | dibutyltin dilaurate                   | 48 mg/m <sup>3</sup>    |
| 14808-60-7  | Quartz (SiO <sub>2</sub> )             | 200 mg/m <sup>3</sup>   |
| 57-55-6     | Propylene glycol                       | 7,900 mg/m <sup>3</sup> |
| 78-83-1     | butanol                                | 8000* ppm               |
| 108-83-8    | 2,6-dimethylheptan-4-one               | 2000* ppm               |
| 108-65-6    | 2-methoxy-1-methylethyl acetate        | 5000* ppm               |
| 34590-94-8  | Dipropylene glycol monomethyl ether    | 9900** ppm              |
| 70657-70-4  | 2-methoxypropyl acetate                | 5,000 ppm               |
| 67-56-1     | methanol                               | 7200* ppm               |

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 5)

- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 123-86-4 n-butyl acetate

|     |   |
|-----|---|
| PEL | Long-term value: 710 mg/m <sup>3</sup> , 150 ppm  |
| REL | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |
| TLV | Short-term value: 150 ppm<br>Long-term value: 50 ppm  |

### 67-64-1 acetone

|     |  |
|-----|--|
| PEL | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm               |
| REL | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm                 |
| TLV | Short-term value: 500 ppm<br>Long-term value: 250 ppm<br>A4, BEI |

### 110-43-0 heptan-2-one

|     |  |
|-----|--|
| PEL | Long-term value: 465 mg/m <sup>3</sup> , 100 ppm |
| REL | Long-term value: 465 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 50 ppm                          |

### 1330-20-7 xylene

|     |   |
|-----|---|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Short-term value: (150) ppm<br>Long-term value: (100) NIC-20 ppm<br>BEI, A4                           |

### 7727-43-7 barium sulphate, natural

|     |   |
|-----|---|
| PEL | Long-term value: 15* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
| REL | Long-term value: 10* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
| TLV | Long-term value: 5* mg/m <sup>3</sup><br>*inhalable fraction; E                 |

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 6)

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI 25 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

USA

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 7)

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Fluid

**Color:** According to product specification

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 55.8-56.6 °C (132.4-133.9 °F)

- **Flash point:** <-18 °C (<-0.4 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 500 °C (932 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

**Lower:** 1.2 Vol %

**Upper:** 13 Vol %

- **Vapor pressure at 20 °C (68 °F):** 233 hPa (174.8 mm Hg)

- **Density at 20 °C (68 °F):** 1.4386 g/cm<sup>3</sup> (12.0051 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

**Water:** Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

**Dynamic:** Not determined.

**Kinematic:** Not determined.

- **Solvent content:**

**Organic solvents:** 47.4 %

**VOC content:** 32.18 %

265.6 g/l / 2.22 lb/gal

**Solids content:** 57.5 %

- **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 8)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
  - **on the skin:** Irritant to skin and mucous membranes.
  - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

| · <b>IARC (International Agency for Research on Cancer)</b> |   |    |
|---|---|----|
| 98-56-6   | 4-chloro-alpha,alpha,alpha-trifluorotoluene                             | 2B |
| 14807-96-6  | Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 3  |
| 1330-20-7   | xylene  | 3  |
| 13463-67-7  | titanium dioxide  | 2B |
| 9002-88-4   | Polyethylene low density  | 3  |
| 112926-00-8   | Precipitated silica (Silica-Amorphous)                                  | 3  |
| 1333-86-4   | Carbon black  | 2B |
| 100-41-4  | ethylbenzene  | 2B |
| 14808-60-7  | Quartz (SiO <sub>2</sub> )  | 1  |

- **NTP (National Toxicology Program)**

|            |                            |   |
|------------|----------------------------|---|
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) | K |
|------------|----------------------------|---|

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
  - **Bioaccumulative potential** No further relevant information available.
  - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
  - **General notes:** Not hazardous for water.
  - **Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

**Trade name: P10 2K DTM PU PRIMER**



(Contd. of page 9)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>   | UN1300   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>IMDG, IATA</b></li> </ul>  | Turpentine substitute<br>TURPENTINE SUBSTITUTE   |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>  | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>   | 3 Flammable liquids<br>3   |
| <ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>  | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>   | 3 Flammable liquids<br>3   |
| <ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>   | II   |
| <ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> </ul>  | Not applicable.  |
| <ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul> | Warning: Flammable liquids<br>33<br>F-E, S-E<br>B  |
| <ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>   | Not applicable.  |

(Contd. on page 11)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 10)

- **Transport/Additional information:**
- **DOT**
- **Quantity limitations**

|  |                                 |
|--|---------------------------------|
|  | On passenger aircraft/rail: 5 L |
|  | On cargo aircraft only: 60 L    |

---

- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN 1300 TURPENTINE SUBSTITUTE, 3, II

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

|           |                          |
|-----------|--------------------------|
| 1330-20-7 | xylene                   |
| 7727-43-7 | barium sulphate, natural |
| 100-41-4  | ethylbenzene             |
| 67-56-1   | methanol                 |

- **TSCA (Toxic Substances Control Act):**

|            |   |        |
|------------|---|--------|
| 98-56-6    | 4-chloro-alpha, alpha, alpha-trifluorotoluene | ACTIVE |
| 123-86-4   | n-butyl acetate                               | ACTIVE |
| 67-64-1    | acetone                                       | ACTIVE |
| 14807-96-6 | Talc (Mg3H2(SiO3)4)                           | ACTIVE |
| 110-43-0   | heptan-2-one                                  | ACTIVE |
| 1330-20-7  | xylene  | ACTIVE |
| 13463-67-7 | titanium dioxide                              | ACTIVE |
| 7727-43-7  | barium sulphate, natural                      | ACTIVE |
| 1332-58-7  | Kaolin  | ACTIVE |
| 9002-88-4  | Polyethylene low density                      | ACTIVE |
| 1333-86-4  | Carbon black                                  | ACTIVE |
| 100-41-4   | ethylbenzene                                  | ACTIVE |
| 77-58-7    | dibutyltin dilaurate                          | ACTIVE |
| 64742-95-6 | Solvent naphtha (petroleum), light arom.      | ACTIVE |
| 14808-60-7 | Quartz (SiO2)                                 | ACTIVE |
| 57-55-6    | Propylene glycol                              | ACTIVE |
| 78-83-1    | butanol                                       | ACTIVE |
| 108-83-8   | 2,6-dimethylheptan-4-one                      | ACTIVE |
| 108-65-6   | 2-methoxy-1-methylethyl acetate               | ACTIVE |

(Contd. on page 12)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 11)

|            |                                     |        |
|------------|-------------------------------------|--------|
| 34590-94-8 | Dipropylene glycol monomethyl ether | ACTIVE |
| 67-56-1    | methanol                            | ACTIVE |

· **Hazardous Air Pollutants**

|           |              |
|-----------|--------------|
| 1330-20-7 | xylene       |
| 100-41-4  | ethylbenzene |
| 67-56-1   | methanol     |

· **Proposition 65**

· **Chemicals known to cause cancer:**

|            |   |
|------------|---|
| 98-56-6    | 4-chloro-alpha,alpha,alpha-trifluorotoluene |
| 13463-67-7 | titanium dioxide                            |
| 1333-86-4  | Carbon black                                |
| 100-41-4   | ethylbenzene                                |
| 14808-60-7 | Quartz (SiO <sub>2</sub> )                  |

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

|         |          |
|---------|----------|
| 67-56-1 | methanol |
|---------|----------|

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

|           |                          |                       |
|-----------|--------------------------|-----------------------|
| 67-64-1   | acetone                  | I                     |
| 1330-20-7 | xylene                   | I                     |
| 7727-43-7 | barium sulphate, natural | D, CBD(inh), NL(oral) |
| 100-41-4  | ethylbenzene             | D                     |

· **TLV (Threshold Limit Value)**

|            |   |    |
|------------|---|----|
| 67-64-1    | acetone   | A4 |
| 14807-96-6 | Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | A4 |
| 1330-20-7  | xylene  | A4 |
| 13463-67-7 | titanium dioxide  | A4 |
| 1332-58-7  | Kaolin  | A4 |
| 1333-86-4  | Carbon black  | A4 |
| 100-41-4   | ethylbenzene  | A3 |
| 77-58-7    | dibutyltin dilaurate  | A4 |
| 14808-60-7 | Quartz (SiO <sub>2</sub> )  | A2 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

|            |                            |
|------------|----------------------------|
| 13463-67-7 | titanium dioxide           |
| 1333-86-4  | Carbon black               |
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) |

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P10 2K DTM PU PRIMER

(Contd. of page 12)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene  
 n-butyl acetate  
 acetone  
 titanium dioxide

- **Hazard statements**

Highly flammable liquid and vapor.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause drowsiness or dizziness.

- **Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

(Contd. on page 14)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

**Trade name: P10 2K DTM PU PRIMER**

(Contd. of page 13)

- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 09/29/2021 / 1
- **Abbreviations and acronyms:**
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - BEI: Biological Exposure Limit
  - Flam. Liq. 2: Flammable liquids – Category 2
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
  - Carc. 2: Carcinogenicity – Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- **\* Data compared to the previous version altered.**

USA