

Safety Data Sheet MATTING

Safety Data Sheet dated 26/1/2018, version 5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Mixture identification:
Trade name: MATTING AGENT
Trade code: T002
Product type and use: tintometric system

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Tintometric system

SU3 Industrial uses: Uses of substances as such or in preparations* at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PC9a Coatings and paints, thinners, paint removers

Uses advised against:

SU21 Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

Company:

Lyquid Specialty Coatings 176 New Highway N. Amityville, NY 11701

Competent person responsible for the safety data sheet:

Phone: (516)736-3476

Emergency telephone number

CHEMTREC

US – 1-800-424-9300 Outside US - +1-703-527-3887 Contract # 994348

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⊠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⊠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⊠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⊠ Warning, STOT SE 3, May cause respiratory irritation.
- ⊠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⊠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.



Safety Data Sheet
MATTING

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash ... Thoroughly after handling.
- P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains

Poly(oxy-1,2-ethandiyl),.alpha.-[(2Z)-3carboxy-1-oxo-2-propenyl]-.omega.-hydroxy-, C9-11-alkyl ethers: May produce an allergic reaction.
 maleic anhydride: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 25% - < 30%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H336 EUH066
>= 12.5% - < 15%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	⚠ 2.6/3 Flam. Liq. 3 H226
>= 12.5% - < 15%	HYDROCARBONS , C9, AROMATICS	EC: 918-668-5 REACH No.: 01-2119455851-35	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 4.1/C2 Aquatic Chronic 2 H411 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.8/3 STOT SE 3 H336 EUH066 DECLP (CLP)*
>= 10% - < 12.5%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.1/4/Dermal Acute Tox. 4 H312



Safety Data Sheet
MATTING

		EC: 215-535-7 REACH No.: 01-2119488216-32	◊ 3.3/2 Eye Irrit. 2 H319 ◊ 3.8/3 STOT SE 3 H335 ◊ 3.2/2 Skin Irrit. 2 H315 ◊ 3.9/2 STOT RE 2 H373 ◊ 3.10/1 Asp. Tox. 1 H304
>= 0.5% - < 1%	Poly(oxy-1,2-ethandiyl),.alpha.-[(2Z)-3carboxy-1-oxo-2-propenyl]-.omega.-hydroxy-, C9-11-alkyl ethers	CAS: 709014-50-6	◊ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317
>= 0.1% - < 0.25%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	◊ 2.6/2 Flam. Liq. 2 H225 ◊ 3.1/4/Inhal Acute Tox. 4 H332 ◊ 3.9/2 STOT RE 2 H373 ◊ 3.10/1 Asp. Tox. 1 H304 4.1/C3 Aquatic Chronic 3 H412
>= 0.1% - < 0.25%	maleic anhydride	Index number: 607-096-00-9 CAS: 108-31-6 EC: 203-571-6 REACH No.: 01-2119472428-31	◊ 3.2/1B Skin Corr. 1B H314 ◊ 3.4.1/1-1A-1B Resp. Sens. 1,1A, 1B H334 ◊ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317 ◊ 3.1/4/Oral Acute Tox. 4 H302
204 ppm	phthalic anhydride	Index number: 607-009-00-4 CAS: 85-44-9 EC: 201-607-5 REACH No.: 01-2119457017-41	◊ 3.8/3 STOT SE 3 H335 ◊ 3.2/2 Skin Irrit. 2 H315 ◊ 3.3/1 Eye Dam. 1 H318 ◊ 3.4.1/1-1A-1B Resp. Sens. 1,1A, 1B H334 ◊ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317 ◊ 3.1/4/Oral Acute Tox. 4 H302

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.



Safety Data Sheet

MATTING

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.



Safety Data Sheet

MATTING

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

OEL 8h - 150 ppm

OEL short - 200 ppm

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

ACGIH - TWA: 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: H

EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: Skin

OEL - TWA: 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm

HYDROCARBONS, C9, AROMATICS

TLV TWA - 100 mg/mq

xylene [4] - CAS: 1330-20-7

MAK - TWA: 100 ppm - STEL: 200 ppm - Notes: D, Skin

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

maleic anhydride - CAS: 108-31-6

ACGIH - TWA(8h): 0.01 mg/m³ - Notes: (IFV), DSEN, RSEN, A4 - Resp sens

phthalic anhydride - CAS: 85-44-9

ACGIH - TWA(8h): 0.002 mg/m³ - STEL: 0.005 mg/m³ - Notes: (IFV), Skin, DSEN,

RSEN, A4 - Resp sens, asthma

DNEL Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Worker Industry: 960 ppm - Consumer: 859.7 ppm - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 960 ppm - Consumer: 859.7 ppm - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 480 ppm - Consumer: 102.34 ppm - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 480 ppm - Consumer: 102.34 ppm - Exposure: Human Inhalation - Frequency: Long Term, local effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 153.5 mg/kg - Consumer: 54.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects



Safety Data Sheet

MATTING

Consumer: 1.67 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

HYDROCARBONS , C9, AROMATICS

Worker Industry: 25 mg/kg - Consumer: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 150 mg/m³ - Consumer: 32 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 11 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

phthalic anhydride - CAS: 85-44-9

Consumer: 5 mg/kg - Exposure: Human Dermal - Notes: die

Worker Professional: 32.2 mg/kg - Consumer: 8.6 mg/kg - Exposure: Human Inhalation - Notes: die

Consumer: 5 mg/kg

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Freshwater sediments - Value: 0.981 mg/kg

Target: Marine water sediments - Value: 0.0981 mg/kg

Target: Soil (agricultural) - Value: 0.0903 mg/kg - Notes: occasional release

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Air - Value: 0.635 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Freshwater sediments - Value: 3.29 mg/kg

Target: Marine water sediments - Value: 0.329 mg/kg

Target: Marine water - Value: 0.0635 mg/l

xylene [4] - CAS: 1330-20-7

Target: Marine water - Value: 0.327 mg/l

Target: Air - Value: 0.327 mg/l - Type of hazard: emissione saltuaria

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Soil (agricultural) - Value: 2.31 mg/kg

phthalic anhydride - CAS: 85-44-9

Target: Microorganisms in sewage treatments - Value: 10 mg/l

Target: Soil (agricultural) - Value: 0.153 mg/kg

Target: Fresh Water - Value: 5.6 mg/l

Target: Marine water sediments - Value: 0.0826 mg/kg

8.2. Exposure controls

Provide adequate ventilation through good general extraction using local exhaust ventilation. If concentrations of solvent or vapor exceed the OEL value, you have to wear respiratory protection.

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:



Safety Data Sheet

MATTING

NBR (nitrile rubber).
 Respiratory protection:
 Mask with filter "A" , brown colour
 Thermal Hazards:
 None
 Environmental exposure controls:
 None
 Appropriate engineering controls:
 None

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	liquid whitish	--	--
Odour:	solvent	--	--
Odour threshold:	solvent	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	25 ° C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	>1	--	--
Relative density:	1.00	--	--
Solubility in water:	none	--	--
Solubility in oil:	soluble	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	tixo	--	--
Explosive properties:	N.A.	--	--



Safety Data Sheet
 MATTING

Oxidizing properties:	N.A.	--	--
-----------------------	------	----	----

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	none	--	--
Fat Solubility:	soluble	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 21.2 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat 10760 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Mouse 8532 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 5001 mg/kg

Test: LC50 - Route: Inhalation - Species: Mouse > 35.7 mg/l - Duration: 4h - Notes: 6 hours

h) STOT-single exposure:

Test: Eye Irritant Positive

Test: Skin Irritant Positive

HYDROCARBONS , C9, AROMATICS

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m³ - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3592 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg

xylene [4] - CAS: 1330-20-7

a) acute toxicity:



Safety Data Sheet

MATTING AGENT

Test: LC50 - Route: Inhalation - Species: Rat 20 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Mouse 5627 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 3500 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 4000 ppm - Duration: 4h

phthalic anhydride - CAS: 85-44-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1530 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 10000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 210 mg/m³ - Duration: 1h

n-butyl acetate - CAS: 123-86-4

LD (RAT) oral, 10770 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

LD50 (RAT) oral. 8532 mg/Kg

LD50 (RAT) derm. >5000 mg/kg

xylene [4] - CAS: 1330-20-7

LD50 (RAT) ORAL: 5000 MG/KG

maleic anhydride - CAS: 108-31-6

LD50 (RAT) ORAL: 481 MG/KG

LD50 (RABBIT) SKIN: 2620 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Do not use when plants are in flower: the product is toxic for bees.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 62 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 205 mg/l - Duration h: 48

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 180 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 380 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 2000 mg/l - Duration h: 72

HYDROCARBONS , C9, AROMATICS

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 9.22 mg/l - Duration h: 96

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Safety Data Sheet

MATTING AGENT

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24
Endpoint: EC50 - Species: Algae = 4.36 mg/l - Duration h: 73
Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96
Endpoint: NOEC - Species: Algae = 0.44 mg/l - Duration h: 73
Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21g
Endpoint: NOEC - Species: Fish = 1.4 mg/l - Notes: 56g

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 1.7 mg/l - Duration h: 96
Endpoint: EC50 - Species: Algae = 2.6 mg/l - Duration h: 72
Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia = 2 mg/l - Duration h: 48

12.2. Persistence and degradability

None

n-butyl acetate - CAS: 123-86-4

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: 83 - Notes: 28 days

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

HYDROCARBONS , C9, AROMATICS

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

xylene [4] - CAS: 1330-20-7

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Bioaccumulation: Not bioaccumulative - Test: N.A. N.A. - Duration h: N.A. - Notes: N.A.

12.4. Mobility in soil

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Mobility in soil: Mobile - Test: N.A. N.A. - Duration h: N.A. - Notes: fast evaporating

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



14.1. UN number

ADR-UN Number: 1263
IATA-UN Number: 1263
IMDG-UN Number: 1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT
IATA-Shipping Name: PAINT
IMDG-Shipping Name: PAINT



Safety Data Sheet

MATTING AGENT

- 14.3. Transport hazard class(es)
- | | |
|-------------------------------------|----|
| ADR-Class: | 3 |
| ADR - Hazard identification number: | 30 |
| IATA-Class: | 3 |
| IATA-Label: | 3 |
| IMDG-Class: | 3 |
- 14.4. Packing group
- | | |
|---------------------|-----|
| ADR-Packing Group: | III |
| IATA-Packing group: | III |
| IMDG-Packing group: | III |
- 14.5. Environmental hazards
- | | |
|------------------------------|----|
| ADR-Environmental Pollutant: | No |
| IMDG-Marine pollutant: | No |
- 14.6. Special precautions for user
- | | |
|---|--------------|
| ADR-Subsidiary risks: | - |
| ADR-S.P.: | 163 640E 650 |
| ADR-Transport category (Tunnel restriction code): | (D/E) |
| IATA-Passenger Aircraft: | 355 |
| IATA-Subsidiary risks: | - |
| IATA-Cargo Aircraft: | 366 |
| IATA-S.P.: | A3 A72 |
| IATA-ERG: | 3L |
| IMDG-EmS: | F-E , S-E |
| IMDG-Subsidiary risks: | - |
| IMDG-Stowage and handling: | Category A |
| IMDG-Segregation: | - |
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
N.A.

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Volatile Organic compounds - VOCs = 656.09 g/l

Volatile CMR substances = 0.03 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.46

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.



Safety Data Sheet

MATTING AGENT

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H411 Toxic to aquatic life with long lasting effects.

H335 May cause respiratory irritation.

H304 May be fatal if swallowed and enters airways.

H332 Harmful if inhaled.

H312 Harmful in contact with skin.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H317 May cause an allergic skin reaction.

H225 Highly flammable liquid and vapour.

H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Resp. Sens. 1,1A,1B	3.4.1/1-1A-1B	Respiratory Sensitisation, Category 1,1A,1B
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3



Safety Data Sheet

MATTING AGENT

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- 4. FIRST AID MEASURES
- 6. ACCIDENTAL RELEASE MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 13. DISPOSAL CONSIDERATIONS
- SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.