



Safety Data Sheet acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

1 Identification

- **Product identifier**
- **Trade name:** P70 2K ACRYLIC PRIMER FILLER
- **Article number:** P70
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lyquid Specialty Coatings
176 New Highway
N. Amityville, NY 11701
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

titanium dioxide
ethylbenzene
dibutyltin dilaurate

- **Hazard statements**

Highly flammable liquid and vapor.
Causes skin irritation.
Suspected of causing cancer. Route of exposure: Inhalation.
May damage fertility or the unborn child.
May cause damage to the hearing organs through prolonged or repeated exposure.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	25-50%
123-86-4	n-butyl acetate	2.5-10%
78-93-3	butanone	2.5-10%
13463-67-7	titanium dioxide	2.5-10%
7727-43-7	barium sulphate, natural	2.5-10%
100-41-4	ethylbenzene	≤2.5%
108-88-3	toluene	≤2.5%
77-58-7	dibutyltin dilaurate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
78-93-3	butanone	200 ppm
13463-67-7	titanium dioxide	30 mg/m ³
7727-43-7	barium sulphate, natural	15 mg/m ³
100-41-4	ethylbenzene	33 ppm
9002-88-4	Polyethylene low density	16 mg/m ³
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m ³
108-88-3	toluene	67 ppm
110-43-0	heptan-2-one	150 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
1333-86-4	Carbon black	9 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

- **PAC-2:**

1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
78-93-3	butanone	2700* ppm
13463-67-7	titanium dioxide	330 mg/m ³
7727-43-7	barium sulphate, natural	170 mg/m ³
100-41-4	ethylbenzene	1100* ppm
9002-88-4	Polyethylene low density	170 mg/m ³
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m ³

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 4)

108-88-3	toluene	560 ppm
110-43-0	heptan-2-one	670 ppm
77-58-7	dibutyltin dilaurate	8 mg/m ³
1333-86-4	Carbon black	99 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

PAC-3:

1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
78-93-3	butanone	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
7727-43-7	barium sulphate, natural	990 mg/m ³
100-41-4	ethylbenzene	1800* ppm
9002-88-4	Polyethylene low density	1,000 mg/m ³
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m ³
108-88-3	toluene	3700* ppm
110-43-0	heptan-2-one	4000* ppm
77-58-7	dibutyltin dilaurate	48 mg/m ³
1333-86-4	Carbon black	590 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

Handling:
Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 5)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI

7727-43-7 barium sulphate, natural

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
-----	--

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 6)

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 NIC-20 ppm
BEI, A3, NIC: OTO, BEI, A3

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, OTO, A4

77-58-7 dibutyltin dilaurate

PEL Long-term value: 0.1 mg/m³
as Sn

REL Long-term value: 0.1 mg/m³
as Sn, Skin

TLV Short-term value: 0.2 mg/m³
Long-term value: 0.1 mg/m³
as Sn; A4; Skin

Ingredients with biological limit values:**1330-20-7 xylene**

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

78-93-3 butanone

BEI 2 mg/L
Medium: urine
Time: end of shift
Parameter: Methyl ethyl ketone (nonspecific)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 7)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Grey
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range: Undetermined.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 8)

Boiling point/Boiling range:	79-80.5 °C (174.2-176.9 °F)
· Flash point:	-4 °C (24.8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7-8.2 hPa (5-6.2 mm Hg)
· Density at 20 °C (68 °F):	1.34 g/cm ³ (11.1823 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	55.5 %
VOC content:	55.55 %
	516.4 g/l / 4.31 lb/gal
Solids content:	33.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 9)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
9002-88-4	Polyethylene low density	3
112926-00-8	Precipitated silica (Silica-Amorphous)	3
108-88-3	toluene	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO ₂)	1

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER



(Contd. of page 10)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | Paint
PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  <p>3</p> </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · IMDG, IATA | |
| <ul style="list-style-type: none"> · Class · Label | <div style="text-align: center;">  <p>3</p> </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | II |
| <ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: | No |
| <ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category | Warning: Flammable liquids
33
F-E, S-E
B |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 11)

- **Transport/Additional information:**
- **DOT**
- **Quantity limitations**

	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)**

	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN 1263 PAINT, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
7727-43-7	barium sulphate, natural
100-41-4	ethylbenzene
108-88-3	toluene

- **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
78-93-3	butanone	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
7727-43-7	barium sulphate, natural	ACTIVE
100-41-4	ethylbenzene	ACTIVE
1332-58-7	Kaolin	ACTIVE
9002-88-4	Polyethylene low density	ACTIVE
108-88-3	toluene	ACTIVE
110-43-0	heptan-2-one	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
1333-86-4	Carbon black	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
57-55-6	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 12)

34590-94-8 Dipropylene glycol monomethyl ether

ACTIVE

· Hazardous Air Pollutants

1330-20-7 xylene

100-41-4 ethylbenzene

108-88-3 toluene

· Proposition 65
· Chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethylbenzene

1333-86-4 Carbon black

14808-60-7 Quartz (SiO₂)
· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

· Carcinogenic categories
· EPA (Environmental Protection Agency)

1330-20-7 xylene

I

78-93-3 butanone

I

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

100-41-4 ethylbenzene

D

108-88-3 toluene

II

· TLV (Threshold Limit Value)

1330-20-7 xylene

A4

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

A4

13463-67-7 titanium dioxide

A4

100-41-4 ethylbenzene

A3

1332-58-7 Kaolin

A4

108-88-3 toluene

A4

77-58-7 dibutyltin dilaurate

A4

1333-86-4 Carbon black

A4

14808-60-7 Quartz (SiO₂)

A2

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

1333-86-4 Carbon black

14808-60-7 Quartz (SiO₂)
· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 13)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

titanium dioxide
ethylbenzene
dibutyltin dilaurate

- **Hazard statements**

Highly flammable liquid and vapor.
Causes skin irritation.
Suspected of causing cancer. Route of exposure: Inhalation.
May damage fertility or the unborn child.
May cause damage to the hearing organs through prolonged or repeated exposure.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Product Safety Dept.

- **Date of preparation / last revision** 09/29/2021 / 1

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 15)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: P70 2K ACRYLIC PRIMER FILLER

(Contd. of page 14)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**

USA