



# Safety Data Sheet

## LEMON YELLOW HIGH COVERAGE

Safety Data Sheet dated 26/1/2018, version 6

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Mixture identification:

Trade name: LEMON YELLOW HIGH COVERAGE

Trade code: T102

Product type and use: tintometric system

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Tintometric system

SU3 Industrial uses: Uses of substances as such or in preparations\* at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PC9a Coatings and paints, thinners, paint removers

Uses advised against:

SU21 Consumer uses: Private households (= general public = consumers)

#### 1.3. Details of the supplier of the safety data sheet

Company:

Lyquid Specialty Coatings 176 New Highway N. Amityville, NY 11701

Competent person responsible for the safety data sheet:

Phone: (516)736-3476

#### 1.4. Emergency telephone number

CHEMTREC

US – 1-800-424-9300 Outside US - +1-703-527-3887 Contract # 994348

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P273 Avoid release to the environment.

P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with applicable regulations.



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

Special Provisions:

None

Contains

Mixture of: butan-2-one oxime: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

### SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 20% - < 25%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	⚠ 2.6/3 Flam. Liq. 3 H226
>= 7% - < 10%	HYDROCARBONS , C9, AROMATICS	EC: 918-668-5 REACH No.: 01-2119455851-35	2.6/3 Flam. Liq. 3 H226 4.1/C2 Aquatic Chronic 2 H411 3.8/3 STOT SE 3 H335 3.10/1 Asp. Tox. 1 H304 3.8/3 STOT SE 3 H336 EUH066 DECLP (CLP)*
>= 7% - < 10%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	2.6/3 Flam. Liq. 3 H226 3.1/4/Inhal Acute Tox. 4 H332 3.1/4/Dermal Acute Tox. 4 H312 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H335 3.2/2 Skin Irrit. 2 H315 3.9/2 STOT RE 2 H373 3.10/1 Asp. Tox. 1 H304
>= 3% - < 5%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336 EUH066



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

>= 0.25% - < 0.5%	Mixture of: butan-2- one oxime	Index number: 616-014-00-0 CAS: 96-29-7 EC: 202-496-6 REACH No.: 01- 2119539477	3.1/4/Dermal Acute Tox. 4 H312 3.3/1 Eye Dam. 1 H318 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317 3.6/2 Carc. 2 H351
----------------------	-----------------------------------	---	--

## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

		-28		
>= 0.25% - < 0.5%	butan-2-ol	Index number: CAS: EC: REACH No.:	603-127-00-5 78-92-2 201-158-5 01-2119475146-36	<ul style="list-style-type: none"> <li>◆ 2.6/3 Flam. Liq. 3 H226</li> <li>◆ 3.3/2 Eye Irrit. 2 H319</li> <li>◆ 3.8/3 STOT SE 3 H335</li> <li>◆ 3.8/3 STOT SE 3 H336</li> </ul>
>= 0.25% - < 0.5%	ethylbenzene	Index number: CAS: EC: REACH No.:	601-023-00-4 100-41-4 202-849-4 01-2119489370-35	<ul style="list-style-type: none"> <li>◆ 2.6/2 Flam. Liq. 2 H225</li> <li>◆ 3.1/4/Inhal Acute Tox. 4 H332</li> <li>◆ 3.9/2 STOT RE 2 H373</li> <li>◆ 3.10/1 Asp. Tox. 1 H304</li> <li>4.1/C3 Aquatic Chronic 3 H412</li> </ul>
260 ppm	phthalic anhydride	Index number: CAS: EC: REACH No.:	607-009-00-4 85-44-9 201-607-5 01-2119457017-41	<ul style="list-style-type: none"> <li>◆ 3.8/3 STOT SE 3 H335</li> <li>◆ 3.2/2 Skin Irrit. 2 H315</li> <li>◆ 3.3/1 Eye Dam. 1 H318</li> <li>◆ 3.4.1/1-1A-1B Resp. Sens. 1,1A, 1B H334</li> <li>◆ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317</li> <li>◆ 3.1/4/Oral Acute Tox. 4 H302</li> </ul>

\*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

#### 4. FIRST AID MEASURES

##### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of Ingestion:

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

#### 5. FIRE-FIGHTING MEASURES

##### 5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

- 5.2. Special hazards arising from the substance or mixture  
Do not inhale explosion and combustion gases.  
Burning produces heavy smoke.
- 5.3. Advice for firefighters  
Use suitable breathing apparatus .  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. ACCIDENTAL RELEASE MEASURES

- 6.1. Personal precautions, protective equipment and emergency procedures  
Wear personal protection equipment.  
Remove all sources of ignition.  
Remove persons to safety.  
See protective measures under point 7 and 8.
- 6.2. Environmental precautions  
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.  
Retain contaminated washing water and dispose it.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.  
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up  
Wash with plenty of water.
- 6.4. Reference to other sections  
See also section 8 and 13

---

#### 7. HANDLING AND STORAGE

- 7.1. Precautions for safe handling  
Avoid contact with skin and eyes, inhalation of vapours and mists.  
Don't use empty container before they have been cleaned.  
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.  
Contaminated clothing should be changed before entering eating areas.  
Do not eat or drink while working.  
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities  
Always keep in a well ventilated place.  
Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.  
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
Keep away from food, drink and feed.  
Incompatible materials:  
None in particular.  
Instructions as regards storage premises:  
Cool and adequately ventilated.
- 7.3. Specific end use(s)  
None in particular

---

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1. Control parameters  
2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
ACGIH - TWA: 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: H  
EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
OEL - TWA: 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm  
HYDROCARBONS , C9, AROMATICS  
TLV TWA - 100 mg/mq



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

xylene [4] - CAS: 1330-20-7  
MAK - TWA: 100 ppm - STEL: 200 ppm - Notes: D, Skin  
EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

n-butyl acetate - CAS: 123-86-4  
ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr  
OEL 8h - 150 ppm  
OEL short - 200 ppm

butan-2-ol - CAS: 78-92-2  
ACGIH - TWA(8h): 100 ppm - Notes: URT irr, CNS impair

ethylbenzene - CAS: 100-41-4  
EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin  
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

phthalic anhydride - CAS: 85-44-9  
ACGIH - TWA(8h): 0.002 mg/m<sup>3</sup> - STEL: 0.005 mg/m<sup>3</sup> - Notes: (IFV), Skin, DSEN, RSEN, A4 - Resp sens, asthma

#### DNEL Exposure Limit Values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
Worker Industry: 153.5 mg/kg - Consumer: 54.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 275 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 1.67 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

#### HYDROCARBONS , C9, AROMATICS

Worker Industry: 25 mg/kg - Consumer: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 150 mg/m<sup>3</sup> - Consumer: 32 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 11 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7  
Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects  
Worker Industry: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects  
Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

n-butyl acetate - CAS: 123-86-4  
Worker Industry: 960 ppm - Consumer: 859.7 ppm - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
Worker Industry: 960 ppm - Consumer: 859.7 ppm - Exposure: Human Inhalation - Frequency: Short Term, local effects  
Worker Industry: 480 ppm - Consumer: 102.34 ppm - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 480 ppm - Consumer: 102.34 ppm - Exposure: Human Inhalation - Frequency: Long Term, local effects

phthalic anhydride - CAS: 85-44-9  
Consumer: 5 mg/kg - Exposure: Human Dermal - Notes: die  
Worker Professional: 32.2 mg/kg - Consumer: 8.6 mg/kg - Exposure: Human Inhalation - Notes: die  
Consumer: 5 mg/kg

#### PNEC Exposure Limit Values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

Target: Air - Value: 0.635 mg/l  
Target: Microorganisms in sewage treatments - Value: 100 mg/l  
Target: Freshwater sediments - Value: 3.29 mg/kg  
Target: Marine water sediments - Value: 0.329 mg/kg  
Target: Marine water - Value: 0.0635 mg/l  
xylene [4] - CAS: 1330-20-7  
Target: Marine water - Value: 0.327 mg/l  
Target: Air - Value: 0.327 mg/l - Type of hazard: emissione saltuaria  
Target: Freshwater sediments - Value: 12.46 mg/kg  
Target: Marine water sediments - Value: 12.46 mg/kg  
Target: Soil (agricultural) - Value: 2.31 mg/kg  
n-butyl acetate - CAS: 123-86-4  
Target: Fresh Water - Value: 0.18 mg/l  
Target: Marine water - Value: 0.018 mg/l  
Target: Freshwater sediments - Value: 0.981 mg/kg  
Target: Marine water sediments - Value: 0.0981 mg/kg  
Target: Soil (agricultural) - Value: 0.0903 mg/kg - Notes: occasional release  
phthalic anhydride - CAS: 85-44-9  
Target: Microorganisms in sewage treatments - Value: 10 mg/l  
Target: Soil (agricultural) - Value: 0.153 mg/kg  
Target: Fresh Water - Value: 5.6 mg/l  
Target: Marine water sediments - Value: 0.0826 mg/kg

#### 8.2. Exposure controls

Provide adequate ventilation through good general extraction using local exhaust ventilation. If concentrations of solvent or vapor exceed the OEL value, you have to wear respiratory protection.

#### Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

#### Protection for skin:

No special precaution must be adopted for normal use.

#### Protection for hands:

NBR (nitrile rubber).

#### Respiratory protection:

Mask with filter "A" , brown colour

Mask FFP1D (OV) short exposure and vapor <TLV (EN 149)

#### Thermal Hazards:

None

#### Environmental exposure controls:

None

#### Appropriate engineering controls:

None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	liquid yellow	--	--
Odour:	solvent	--	--
Odour threshold:	solvent	--	--
pH:	N.A.	--	--
Melting point / freezing	n.d.	--	--



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

point:			
Initial boiling point and boiling range:	n.d.	--	--
Flash point:	25 ° C	--	--
Evaporation rate:	n.d.	--	--
Solid/gas flammability:	n.a.	--	--
Upper/lower flammability or explosive limits:	0.7-8.5% (min max) VV	--	--
Vapour pressure:	n.d.	--	--
Vapour density:	>1	--	--
Relative density:	1.14	--	--
Solubility in water:	nessuno	--	--
Solubility in oil:	soluble	--	--
Partition coefficient (n-octanol/water):	n.d.	--	--
Auto-ignition temperature:	n.d.	--	--
Decomposition temperature:	n.d.	--	--
Viscosity:	6000 cP	--	--
Explosive properties:	n.d.	--	--
Oxidizing properties:	n.d.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	none	--	--
Fat Solubility:	soluble	--	--
Conductivity:	n.d.	--	--
Substance Groups relevant properties	N.A.	--	--

---

## 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

T102/6

Page n. 8 of 13





## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products  
None.

---

## 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Mouse 8532 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 5001 mg/kg

Test: LC50 - Route: Inhalation - Species: Mouse > 35.7 mg/l - Duration: 4h - Notes: 6 hours

h) STOT-single exposure:

Test: Eye Irritant Positive

Test: Skin Irritant Positive

HYDROCARBONS , C9, AROMATICS

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m3 - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3592 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat 20 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Mouse 5627 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 21.2 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat 10760 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

Mixture of: butan-2-one oxime - CAS: 96-29-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 20 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 2528 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 1000 mg/kg

butan-2-ol - CAS: 78-92-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 6480 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 48.5 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 3500 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 4000 ppm - Duration: 4h

phthalic anhydride - CAS: 85-44-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1530 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 10000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 210 mg/m3 - Duration: 1h

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

T102/6

Page n. 9 of 13



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

LD50 (RAT) oral. 8532 mg/Kg  
LD50 (RAT) derm. >5000 mg/kg  
xylene [4] - CAS: 1330-20-7  
LD50 (RAT) ORAL: 5000 MG/KG

n-b utyl acetate - CAS: 123-86-4  
LD (RAT) oral, 10770 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

## 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Do not use when plants are in flower: the product is toxic for bees.

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 180 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 380 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 2000 mg/l - Duration h: 72

HYDROCARBONS , C9, AROMATICS

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 9.22 mg/l - Duration h: 96

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae = 4.36 mg/l - Duration h: 73

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: NOEC - Species: Algae = 0.44 mg/l - Duration h: 73

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21g

Endpoint: NOEC - Species: Fish = 1.4 mg/l - Notes: 56g

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 62 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 205 mg/l - Duration h: 48

butan-2-ol - CAS: 78-92-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 3670 mg/l - Duration h: 96 - Notes: pimephales promelas

Endpoint: EC50 - Species: Daphnia = 3752 mg/l - Duration h: 24 - Notes: daphnia magna

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 1.7 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.6 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 2 mg/l - Duration h: 48

### 12.2. Persistence and degradability



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

- None
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- HYDROCARBONS , C9, AROMATICS  
Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- xylene [4] - CAS: 1330-20-7  
Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- n-butyl acetate - CAS: 123-86-4  
Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: 83 - Notes: 28 days
- 12.3. Bioaccumulative potential  
2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
Bioaccumulation: Not bioaccumulative - Test: N.A. N.A. - Duration h: N.A. - Notes: N.A.
- 12.4. Mobility in soil  
2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
Mobility in soil: Mobile - Test: N.A. N.A. - Duration h: N.A. - Notes: fast evaporating
- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects  
None

---

### 13. DISPOSAL CONSIDERATIONS

- 13.1. Waste treatment methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

### 14. TRANSPORT INFORMATION



- 14.1. UN number  
ADR-UN Number: 1263  
IATA-UN Number: 1263  
IMDG-UN Number: 1263
- 14.2. UN proper shipping name  
ADR-Shipping Name: PAINT  
IATA-Shipping Name: PAINT  
IMDG-Shipping Name: PAINT
- 14.3. Transport hazard class(es)  
ADR-Class: 3  
ADR - Hazard identification number: 30  
IATA-Class: 3  
IATA-Label: 3  
IMDG-Class: 3
- 14.4. Packing group  
ADR-Packing Group: III  
IATA-Packing group: III  
IMDG-Packing group: III
- 14.5. Environmental hazards  
ADR-Environmental Pollutant: No  
IMDG-Marine pollutant: No



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

- 14.6. Special precautions for user
- |   |              |
|---|--------------|
| ADR-Subsidiary risks:                                   | -            |
| ADR-S.P.:   | 163 640E 650 |
| ADR-Transport category (Tunnel restriction code): (D/E) |              |
| IATA-Passenger Aircraft:                                | 355          |
| IATA-Subsidiary risks:                                  | -            |
| IATA-Cargo Aircraft:                                    | 366          |
| IATA-S.P.:  | A3 A72       |
| IATA-ERG:   | 3L           |
| IMDG-EmS:   | F-E , S-E    |
| IMDG-Subsidiary risks:                                  | -            |
| IMDG-Stowage and handling:                              | Category A   |
| IMDG-Segregation:                                       | -            |
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
N.A.

---

## 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Volatile Organic compounds - VOCs = 486.89 g/l

Volatile CMR substances = 0.04 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.40 %

Organic Carbon - C = 0.29

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

---

## 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H411 Toxic to aquatic life with long lasting effects.

H335 May cause respiratory irritation.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H332 Harmful if inhaled.

H312 Harmful in contact with skin.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H318 Causes serious eye damage.



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H225 Highly flammable liquid and vapour.  
H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H302 Harmful if swallowed.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Resp. Sens. 1,1A,1B	3.4.1/1-1A-1B	Respiratory Sensitisation, Category 1,1A,1B
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification  
SECTION 3: Composition/information on ingredients  
5. FIRE-FIGHTING MEASURES  
7. HANDLING AND STORAGE  
8. EXPOSURE CONTROLS/PERSONAL PROTECTION  
13. DISPOSAL CONSIDERATIONS  
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:



## Safety Data Sheet

### LEMON YELLOW HIGH COVERAGE

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.